


600V Super Junction Power MOSFET
Features

- Low drain-source on-resistance: $R_{DS(ON)}=0.14\Omega(\text{typ})$
- Easy to control gate switching
- Enhancement mode: $V_{th} = 2.5$ to 3.5V
- 100% avalanche tested
- RoHS compliant

Applications

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)
- Charger, Lighting

Pin Description


V_{DSS}	600	V
$R_{DS(ON)-Typ}$	140	m Ω
I_D	20	A

Absolute Maximum Ratings ($T_J=25^\circ\text{C}$, Unless Otherwise Noted)

Symbol	Parameter	N-Channel	Unit
V_{DSS}	Drain-Source Voltage	600	V
V_{GSS}	Gate-Source Voltage	± 30	V
T_J	Maximum Junction Temperature	-55 to 150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$
E_{AS}	Single Pulse Avalanche Energy ^③	480	mJ
$I_{DM}^{①}$	Pulse Drain Current Tested	60	A
I_D	Continuous Drain Current	$T_C=25^\circ\text{C}$	A
P_D	Maximum Power Dissipation	$T_C=25^\circ\text{C}$	W

Thermal Characteristics

Symbol	Parameter	Rating	Unit
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient	62	$^\circ\text{C}/\text{W}$
$R_{\theta JC}$	Thermal Resistance Junction-Case ^①	0.83	$^\circ\text{C}/\text{W}$

Note ① : Max. current is limited by bonding wire.

Note ② : UIS tested and pulse width are limited by maximum junction temperature 150°C .

Note ③ : Surface Mounted on 1in^2 FR-4 board with 1oz.









600V Super Junction Power MOSFET




Electrical Characteristics ($T_J=25^{\circ}\text{C}$, Unless Otherwise Noted)


Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Static Electrical Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	600	---	---	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=200V, V_{GS}=0V$	---	---	1	μA
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2.5	---	3.5	V
I_{GSS}	Gate Leakage Current	$V_{GS}=\pm 30V, V_{DS}=0V$	---	---	± 100	nA
$R_{DS(on)}$	Drain-Source On-state Resistance	$V_{GS}=10V, I_D=10A$	---	140	160	$m\Omega$
Dynamic Characteristics ^⑤						
C_{iss}	Input Capacitance	$V_{GS}=0V,$ $V_{DS}=100V,$ Freq.=1MHz	---	1724	---	pF
C_{oss}	Output Capacitance		---	72	---	
C_{rss}	Reverse Transfer Capacitance		---	6	---	
$T_{d(on)}$	Turn-on Delay Time	$V_{DD}=400V, I_D=20A,$ $V_{GS}=10V, R_G=25\Omega$	---	25	---	nS
T_r	Turn-on Rise Time		---	59	---	
$T_{d(off)}$	Turn-off Delay Time		---	121	---	
T_f	Turn-off Fall Time		---	44	---	
Q_g	Total Gate Charge	$V_{DS}=400V, V_{GS}=10V,$ $I_D=20A$	---	38.5	---	nC
Q_{gs}	Gate-Source Charge		---	8	---	
Q_{gd}	Gate-Drain Charge		---	15	---	
Source-Drain Characteristics ($T_J=25^{\circ}\text{C}$)						
V_{SD}	Diode Forward Voltage _z	$V_{GS}=0V, I_S=20A, T_J=25^{\circ}\text{C}$	---	0.9	1.2	V
t_{rr}	Reverse Recovery Time	$V_R=400V, I_F=20A,$ $di/dt=100A/\mu s, T_J=25^{\circ}\text{C}$	---	453	---	nS
Q_{rr}	Reverse Recovery Charge		---	5.1	---	nC

Note ④ : Pulse test (pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$).

Note ⑤ : Guaranteed by design, not subject to production testing.

600V Super Junction Power MOSFET
Typical Characteristics

Figure 1. Output Characteristics

Figure 2. Transfer Characteristics

Figure 3. On-Resistance vs. Drain Current

Figure 4. Capacitance

Figure 5. Gate Charge

Figure 6. Body Diode Forward Voltage

600V Super Junction Power MOSFET

Figure 7. On-Resistance vs. Junction Temperature

Figure 8. Breakdown voltage vs. Junction Temperature

Figure 9. Transient Thermal Impedance TO-220/TO-263

600V Super Junction Power MOSFET
TO-220 Package Outline Data


Symbol	Dimensions In Millimeters	
	Min.	Max.
A	4.350	4.650
A1	2.250	2.550
b	0.710	0.910
b1	1.170	1.400
c	0.330	0.650
c1	1.200	1.400
D	9.910	10.250
E	8.9500	9.750
E1	12.650	12.950
e	2.540 TYP.	
e1	4.980	5.180
F	2.650	2.950
H	7.900	8.100
h	0.000	0.300
L	12.700	13.500
L1	2.850	3.250
V	7.500 REF.	
Φ	3.400	3.800