


650V Super Junction Power MOSFET
Features

- Low drain-source on-resistance: $R_{DS(ON)}=0.32\Omega(\text{typ})$
- Easy to control gate switching
- Enhancement mode: $V_{th} = 2$ to $4V$
- 100% avalanche tested
- RoHS compliant

Applications

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)
- Charger, Lighting

Pin Description


V_{DSS}	650	V
$R_{DS(ON)-Typ}$	320	m Ω
I_D	11	A

Absolute Maximum Ratings ($T_J=25^\circ\text{C}$, Unless Otherwise Noted)

Symbol	Parameter	Rating	Unit
V_{DSS}	Drain-Source Voltage	650	V
V_{GSS}	Gate-Source Voltage	± 30	V
T_J	Maximum Junction Temperature	-55 to 150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$
E_{AS}	Single Pulse Avalanche Energy ^③	320	mJ
$I_{DM}^{①}$	Pulse Drain Current Tested	30	A
I_D	Continuous Drain Current	$T_C=25^\circ\text{C}$	A
P_D	Maximum Power Dissipation	$T_C=25^\circ\text{C}$	W

Thermal Characteristics

Symbol	Parameter	Rating	Unit
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient	62	$^\circ\text{C}/\text{W}$
$R_{\theta JC}$	Thermal Resistance Junction-Case ^①	1.6	$^\circ\text{C}/\text{W}$

Note ① : Max. current is limited by bonding wire.

Note ② : UIS tested and pulse width are limited by maximum junction temperature 150°C .







Note ③ : Surface Mounted on 1in^2 FR-4 board with 1oz.

**650V Super Junction Power MOSFET****Electrical Characteristics** ($T_J=25^{\circ}\text{C}$, Unless Otherwise Noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Static Electrical Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	650	---	---	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=600V, V_{GS}=0V$	---	---	1	μA
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2	---	4	V
I_{GSS}	Gate Leakage Current	$V_{GS}=\pm 30V, V_{DS}=0V$	---	---	± 100	nA
$R_{DS(ON)}$	Drain-Source On-state Resistance	$V_{GS}=10V, I_D=5.5A$	---	320	380	$m\Omega$
Dynamic Characteristics ^⑤						
C_{iss}	Input Capacitance	$V_{GS}=0V,$ $V_{DS}=100V,$ Freq.=1MHz	---	797	---	pF
C_{oss}	Output Capacitance		---	30	---	
C_{rss}	Reverse Transfer Capacitance		---	4.2	---	
$T_{d(on)}$	Turn-on Delay Time	$V_{DD}=400V, V_{GS}=10V,$ $R_G=25\Omega, I_D=5.5A$	---	41	---	nS
T_r	Turn-on Rise Time		---	20	---	
$T_{d(off)}$	Turn-off Delay Time		---	120	---	
T_f	Turn-off Fall Time		---	20	---	
R_g	Gate Resistance	$f = 1.0\text{MHz},$ open drain	---	14	---	Ω
Q_g	Total Gate Charge	$V_{DS}=400V, V_{GS}=10V,$ $I_D=5.5A$	---	20	---	nC
Q_{gs}	Gate-Source Charge		---	4.2	---	
Q_{gd}	Gate-Drain Charge		---	7	---	
Source-Drain Characteristics ($T_J=25^{\circ}\text{C}$)						
V_{SD} ^④	Diode Forward Voltage	$I_S=5.5A, V_{GS}=0V$	---	0.9	1.2	V
t_{rr}	Reverse Recovery Time	$V_R=400V, I_F=5.5A,$ $di/dt=100A/\mu s, T_J=25^{\circ}\text{C}$	---	330	---	nS
Q_{rr}	Reverse Recovery Charge		---	3.5	---	nC

Note ④ : Pulse test (pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$).

Note ⑤ : Guaranteed by design, not subject to production testing.

650V Super Junction Power MOSFET
Typical Characteristics

Figure 1. Output Characteristics

Figure 2. Transfer Characteristics

Figure 3. On-Resistance vs. Drain Current

Figure 4. Capacitance

Figure 5. Gate-to-Source Voltage vs. Total Gate Charge

Figure 6. Body Diode Forward Voltage


650V Super Junction Power MOSFET


Figure 7. On-Resistance vs. Junction Temperature




Figure 8. Threshold Voltage vs. Junction Temperature





Figure 9. Transient Thermal Impedance

650V Super Junction Power MOSFET
TO-252 Package Outline Dimensions


Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	2.25	2.65	0.089	0.104
A1	0.00	0.15	0.000	0.006
A2	2.20	2.40	0.087	0.094
b	0.50	0.70	0.020	0.028
b1	0.70	0.90	0.028	0.035
c	0.46	0.66	0.018	0.026
c1	0.46	0.66	0.018	0.026
D	6.30	6.70	0.248	0.264
D1	5.20	5.40	0.205	0.213
E	5.30	5.70	0.209	0.224
E1	1.40	1.60	0.055	0.063
H	9.40	9.90	0.370	0.390
e	2.30 TYP		0.09 TYP	
L	1.40	1.77	0.055	0.070
L1	0.50	0.70	0.020	0.028
theta	0°	8°	0°	8°